

3,000 LBS WINCHES

NEW ITEMS IN BLUE | UPDATED APPLICATIONS IN RED








ALL WINCHES INCLUDE A UNIVERSAL MOUNTING BRACKET, HARDWARE, HANDLEBAR SWITCH, AND ELECTRICAL CONNECTIONS AS FEATURED BELOW

GENERATION





AC-12019 SERIES




WINCH









SPECIFICATIONS

JI ECII IONI IONO				
RATED LINE PULL	3,000 LBS. (1,360KGS.) SINGLE-LINE			
MOTOR	12V DC, 1.0HP (770W) PERMANENT MAGNET			
CONTROLS	TROLS HANDLEBAR MOUNTED MINI-ROCKER SWITCH			
GEARING 3-STAGE PLANETARY				
LUTCH (FREESPOOLING) CAM ACTIVATED				
BRAKE	AKE MECHANICAL BRAKE			
DRUM DIAMETER/ LENGTH	20" /2,9"			
ROPE (in X ft) (mm X m)	AC-12016 SERIES: STEEL WIRE, 3/16" X 50' (4.8MM X 15.2M)			
	AC-12019 SERIES: SYNTHETIC ROPE, 3/14" X 33' (5.5MM X 10M)			
FAIRLEAD	ROLLER			
GEAR RATIO	136 : 1			
RECOMMENDED BATTERY	BATTERY 12 AMP/HOUR MINIMUM FOR WINCHING			

PERFORMANCE DATA

LAYER	RATED LINE PULL LBS (KGS)	TOTAL ROPE ON DRUM FT (M)	LINE PULL LBS (KGS)	LINE SPEED	MOTOR (DRAW)
1	3,000 (1,361)	8.85 (2.7)	0	27ft (8.3m)	15 AMPS
2	2,561 (1,162)	19.22 (5.86)	500 (227)	20ft (6.1m)	40 AMPS
3	2,234 (1,013)	31.11 (9.48)	1,000 (454)	14ft (4.3m)	60 AMPS
4	1,981 (899)	44.52 (13.58)	2,000 (907)	9ft (2.7m)	130 AMPS
5	1,779 (807)	50.00 (15.2)	3,000 (1361)	5ft (1.5m)	190 AMPS