

4,500 LBS WINCHES

NEW ITEMS IN BLUE | UPDATED APPLICATIONS IN RED







ALL WINCHES INCLUDE A UNIVERSAL MOUNTING BRACKET, HARDWARE, HANDLEBAR SWITCH, AND ELECTRICAL CONNECTIONS AS FEATURED BELOW

AC-12107 SERIES



AC-12108 SERIES
















SPECIFICATIONS

SPECIFICATIONS				
RATED LINE PULL	4,500 LBS. (2,045KGS.) SINGLE-LINE			
MOTOR	12V DC, 1.3HP PERMANENT MAGNET			
BRAKE	MECHANICAL BRAKE			
DRUM LENGTH	120MM			
ROPE (in X ft) (mm X m) AC-12107 SERIES: STEEL WIRE, 3/14" X 50' (5.5MM X 15.2M)				
	AC-12108 SERIES: SYNTHETIC ROPE, 3/14" X 33' (5.5MM X 15.5M)			
FAIRLEAD	ROLLER ROLLER			
GEAR RATIO	166 : 1			
OVERALL DIMENSIONS (LxWxH)	VERALL DIMENSIONS (L x W x H) 395X117X120MM			

PERFORMANCE DATA

LAYER	RATED LINE PULL	TOTAL ROPE ON DRUM	LINE PULL	LINE	MOTOR
	LBS (KGS)	FT (M)	LBS (KGS)	SPEED	(DRAW)
1	4,500 (2,041)	7.22 (2.2)	0(N/A)	24.11ft (7.35m)	26 AMPS
2	3,700 (1,678)	16.08 (4.9)	1,125 (511)	14.27ft (4.35m)	109 AMPS
3	3,200 (1,451)	26.57 (8.1)	2,250 (1,022)	9.31ft (2.84m)	155 AMPS
4	2,800 (1,270)	39.37 (12)	3,375 (1,534)	6.88ft (2.1m)	196 AMPS
5	2,540 (1,152)	50.0 (15.2)	4,500 (2,045)	5.41ft (1.65m)	238 AMPS