

6,000 LBS WINCHES

NEW ITEMS IN BLUE | UPDATED APPLICATIONS IN RED







ALL WINCHES INCLUDE A UNIVERSAL MOUNTING BRACKET, HARDWARE, HANDLEBAR SWITCH, AND ELECTRICAL CONNECTIONS AS FEATURED BELOW

AC-12134 SERIES



AC-12135 SERIES




















SPECIFICATIONS

JI LOI I GATIONS				
RATED LINE PULL	E PULL 6,000 LBS. (2,722KGS.) SINGLE-LINE			
MOTOR	12V			
BRAKE	MECHANICAL BRAKE			
DRUM LENGTH	JM LENGTH 120MM			
ROPE (in X ft) (mm X m) AC-12134 SERIES: STEEL WIRE, 1/4" X 49' (6.4MM X 15.2M)				
	AC-12135 SERIES: SYNTHETIC ROPE, 15/64" X 49' (6MM X 15.2M)			
FAIRLEAD	ROLLER			
GEAR RATIO	226 : 1			
OVERALL DIMENSIONS (LxWxH)	372x118x124mm			

PERFORMANCE DATA

TERI ORPIANCE DATA							
LAYER	RATED LINE PULL	TOTAL ROPE ON DRUM	LINE PULL	LINE	MOTOR		
	LBS (KGS)	FT (M)	LBS (KGS)	SPEED	(DRAW)		
1	6,000 (2,722)	11.15 (3.4)	0 (N/A)	18ft (5.5m)	29 AMPS		
2	4,878 (2,217)	22.47 (6.85)	1,000 (454)	15ft (4.6m)	59 AMPS		
3	4,279 (1,945)	36.64 (11.17)	3,000 (1,361)	10ft (3.1m)	116 AMPS		
4	3,396 (1,543)	55.1 (16.8)	4,000 (1,814)	8ft (2.4m)	155 AMPS		
5			5,000 (2,268)	5ft (1.5m)	211 AMPS		
6			6,000 (2,722)	3.5ft (1.1m)	277 AMPS		